



TamTeek

All In 1

Wood Adhesive



HIGH-PERFORMANCE WOOD ADHESIVE

Strong | Durable | Versatile

Description:

TAMTEEK ALL IN 1 – Wood Adhesive
High-performance, ready-to-use adhesive for strong & durable bonding of wood with multiple substrates. Suitable for interior & exterior applications.

Applications

Wood to laminate
Wood to PVC sheet
Wood to charcoal sheet
Wood to granite & marble
Wood to glass & steel
Wood to ACP (Aluminium Composite Panel)
Wood to aluminium surfaces

Key Features

Excellent bonding strength & durability
Waterproof & moisture resistant
Good heat resistance
Fast initial tack & quick setting
High coverage with smooth spreadability
High solid content for superior performance
Non-corrosive & non-toxic
Works on porous & non-porous surfaces

Application Method

Clean & dry surfaces thoroughly
Mix adhesive well before use
Apply evenly using brush / roller / spreader
Join surfaces immediately and press firmly
Initial bonding: 6–8 hours
Full strength: 24 hours

Coverage

40–45 sq.ft. per Kg

Packaging

1 Kg, 2 Kg, 5 Kg, 10 Kg, 20 Kg, 30 Kg & 50 Kg buckets

Storage & Shelf Life

Store in cool, dry place (5°C–35°C)
Keep container tightly closed
Shelf life: 12 months (unopened)

Health & Safety

Use gloves & eye protection
Avoid skin/eye contact
Keep away from children

Technical Specification

Appearance	White liquid
Viscosity	4200 to 5000 mPa.
PH	4.0 to 6.0
Solid Content %	55 ± 2%

