



# TamTeek

## MWP

Wood Adhesive



### PREMIUM QUALITY SYNTHETIC RESIN-BASED ADHESIVE

Designed For Woodwork Applications

#### Description:

TAMTEEK MWP – Premium Wood Adhesive  
Synthetic resin-based high-performance adhesive for woodworking applications, offering excellent bonding strength and very high water resistance, suitable even for marine-grade plywood after proper curing.

#### Applications

Laminates, plywood, veneers  
Particleboard, MDF, block board & hard board  
Wooden cabinets (TV, radio, furniture)  
Wooden frames & general carpentry works  
Wood components in bus body construction

#### Key Features

Solvent-free, non-hazardous & non-flammable  
Odour-free formulation  
High water & moisture resistance  
Fast setting – handling strength in 4–6 hours  
Smooth flow & high coverage  
Forms clear, uniform film after drying  
Easy to clean while wet

#### Application Method

Surfaces must be clean, dry & grease-free  
Lightly roughen surfaces  
Stir adhesive well before use  
Apply evenly (less porous surface first, then porous)  
Press and align immediately  
Positioning time: 5–6 minutes  
Keep under pressure for best results  
(release after 4–6 hours)

#### Coverage

Approx. 34–38 sq.ft./kg (both side application)

#### Packaging

1, 2, 5, 10, 20, 30 & 50 kg buckets

#### Storage & Shelf Life

Store in cool, dry place  
Shelf life: 12 months from manufacture

#### Health & Safety

Avoid eye & prolonged skin contact  
Wash with water if contact occurs  
Do not ingest  
Keep out of reach of children

#### Technical Specification

Appearance	<b>Milky white emulsion</b>
Viscosity at 30 °C, Poise	<b>250 to 325</b>
PH	<b>3.0 to 5.0</b>
Specific Gravity	<b>1.05 to 1.09</b>
Flow	<b>Continuous</b>
Spread ability	<b>Smooth and Easy</b>

